Fitting Instructions

Toyota 75, 78, 76 Vehicle

Year

Wheel On Door Type and HF Aerial

Bracket

Part

Date published February 5, 2020

Applicable to Part Numbers K7124, K7125

FITTING INSTRUCTIONS WHEEL ON DOOR BRACKET and HF BRACKET (K7124 and K7125) Suitable for TOYOTA 75/78, 76 SERIES



- 1. Remove wheel and wheel mount bracket from door.
- 2. Fit main silver bracket between door and wheel mount bracket using M10 x 1.25 x 30 bolt, spring and flat. TIGHTEN ALL BOLTS.
- 3. Fit telescopic light bracket using two M10 x 30 bolts, spring and flat washers.





90 Beresford Road, Lilydale, Vic, 3140, Australia www.kaymar.com.au sales@kaymar.com.au P: +61 3 9739 4110 F: +61 3 9739 4111

IXAYIMAI Fitting Instructions

4. If an H/F Aerial bracket is to be fitted. Remove telescopic light bracket and fit H/F aerial bracket. This sits in between main silver bracket and telescopic light bracket. Re-fit bolts.



5. Using a 9mm drill bit, drill two holes through wheel mount bracket using H/F aerial bracket as a guide. Fit using M8 x 20 flat, spring washers and nuts.



